

3150 Arden Road, NW 3rd Floor • Atlanta, GA 30350 • (888) 476-4530 Corporate e-mail: contact@soogalu.com • <u>www.soogalu.com</u>

SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	Soogalu Orthodontic Wire
Product Description	Stainless Steel Wire, all grades
Manufacturer	Soogalu 3150 Arden Road, NW 3 rd Floor Atlanta, GA 30305 888-476-4530 Emergency Phone Number: Infotrac: 888-476-4530
Recommended use	Professional use: Product is intended for the manufacturing of orthodontic appliances.
Restrictions on use	N/A
2. HAZARDS IDENTIFICATION	
Hazard classification	Physical
Hazard classification Signal Word	Physical N/A
	-

Other hazards

3. COMPOSTITION/INFORMATION ON INGREDIENTS

Statement for unknown toxicity Steel products in their natural state do not present an inhalation or contact hazard, however operations such as burning or welding, sawing, brazing and grinding may release fumes and or dust, which may present health hazards. There is not an American Conference of Governmental Industrial Hygienists (ACGIH) threshold limit value (TLV) or OSHA exposure limit (PEL) established for steel.

Chemical name

Common name/synonyms

See graph below

Various Stainless-Steel Products

Impurities and stabilizing additives*

Component	CAS #	Percent	OSHA PEL(mg/m ³)	ACGIH TLV (mg/m3)
Iron	7439-89-6	45 - 90	10 mg/ m ³ Iron Oxide – Fume	10 mg/ m ³ Iron Oxide – Dust & Fume
Nickel	7440-02-2	0 - 40	1 mg/m ³ , Metal, soluble & insoluble compounds	1.5 mg/ m ³ Metal 0.1 mg/ m ³ Soluble compounds 0.2 mg/ m ³ , Insoluble compounds
Chromium	7440-47-3	10.5 – 30	1 mg/ m ³ , Metal & insoluble salt 0.5 mg/m ³ , Cr (III) 5 μg/m ³ , Cr (VI) 2.5 μg/m ³ Action Level Cr (VI)	0.5 mg/m ³ Metal and Cr (III) 0.05 mg/m ³ , Cr (VI) & water soluble compounds 0.01 mg/m ³ , Cr (VI) Insoluble compounds
Manganese	7439-96-5	0-15	5 mg/m ³ (ceiling)	0.2 mg/m ³
Molybdenum	7429-98-7	0-5	5 mg/m ³ Soluble compounds as MO 15 mg/m ³ Total dust	5 mg/m ³ Soluble compounds as MO 10 mg/m ³ Insoluble compounds as MO
Copper	7440-50-8	0-5	0.1 mg/m ³ Fume 1.0 mg/m ³ Dust & Mist	0.2 mg/m ³ Fume 1.0 mg/m ³ Dust & Mist
Silicon	7440-21-3	0-3	15 mg/m ³ Total dust 5 mg/m ³ Respirable dust	10 mg/m ³ Total dust
Aluminum	7429-90-5	0-1	15 mg/m ³ Metal & Total dust 5 mg/m ³ Respirable dust	1 mg/m ³ Respirable dust 5 mg/m ³ Welding fume
Cobalt	7440-48-4	0 – 1	0.1 mg/m ³ Metal, Dust & Fume	0.02 mg/m [°] Metal, Dust & Furne
Vanadium	1314-62-1	Trace	0.5 mg/m ³ (ceiling) Vanadium Pentoxide dust 0.1 mg/m ³ (ceiling) Vanadium Pentoxide fume	0.05 mg/m ³ Vanadium Pentoxide

Tungsten	7440-33-7	Trace	15mg/m ³ Total Dust 5 mg/m ³ Respirable dust	1.0 mg/m ³ 3 mg/m ³ STEL Soluble 5.0 mg/m ³ 10 mg/m ³ STEL Insoluble
Tantalum	7440-25-7	Trace	5 mg/m ³ Metal & Oxide dust	5 mg/m ³ Metal & Oxide dust
1 citicataini		nuoo	10 mg/m ³ STEL	o mg m motor di o mao ador
Titanium	7440-32-6	0 – 1	15 mg/m³ Titanium Dioxide	10 mg/m ³ Titanium Dioxide total
			total dust	dust
Lead	7439-92-1	Trace	0.05 mg/m ³	0.05 mg/m ³

*Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required.

4. FIRST AID MEASURES

Description of First Aid Measures

InhalationRemove from dusty area to fresh air. If discomfort
persists, consult physician.Skin ContactIf irritation develops, wash skin thoroughly with
soap and water. Seek medical attention, if
necessary.Eye ContactWash with copious amounts of water for 15 minutes
to ensure that no articles remain in the eye. Seek
medical advice if irritation persists.IngestionIf significant amounts of dusts are ingested consult
physician.

Most important symptoms or effects, both acute and delayed:

N/A

Indication of immediate medical attention and special treatment needed:

N/A

5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	For solid formed alloy, as appropriate for surrounding fire. A fire involving finely divided alloy should be treated as class D combustible metal fire. Fire should be extinguished by a properly trained and experienced firefighter. Proper care should be taken in applying extinguishing agent.
Unsuitable extinguishing media	Solid formed alloy does not constitute a fire explosion hazard. However, finely divided, suspended particulates may present a fire and explosion hazard in the presence of an ignition source.

Special hazards arising from substance	Not applicable for solid formed alloy. Toxic metal and metallic oxide fumes may be evolved from fires involving finely divided alloy.
Special protective equipment and Precautions for fire fighters	For solid formed alloy, as appropriate for surrounding fire. Positive pressure SCBE and structural firefighter's protective clothing should be used at a minimum for surrounding fire.
6. ACCIDEDNTAL RELEASE MEASURE	ES

Personal precautions, protective equipment and emergency procedures	Respiratory: NIOSH/MSHA-approved dust/mist/fume respiratory should be used during welding, burning, and grinding operations, if applicable exposure limits are exceeded. Gloves: Suitable for protection against physical injury and skin contact during handling and processing. Eyes: Safety glasses or goggles should be worn when there is a probability of flying particles or elevated levels of dust or fume.
Environmental precautions	Shut off ignition source, no flares, smoking or flames should be in or near hazard area. Do not touch or walk through spilled material. Clean up using methods which avoid dust generation. Compressed air should not be used. During cleanup avoid inhalation and skin and eye contact. Provide local exhaust or dilution ventilation as required.
Methods and materials for containment and cleaning up	Dispose of in accordance with all applicable federal, state and local regulations
7. HANDLING AND STORAGE	
Handling	Avoid breathing of and contact with fumes and dusts during processing. No specific requirements for solid formed steel product
Storage	Keep away from incompatible materials.
Storage temperature	N/A
Incompatible materials	Oxidizers. Reacts with strong acids to form explosive hydrogen gas.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OSHA Permissible Exposure Limits N/A

ACGIH Threshold Limit Values Other limitations recommended by manufacturer	N/A N/A
Appropriate Engineering Controls	Local and or general exhaust ventilation should be used to keep worker exposure below applicable exposure limits (section 2) during welding, brazing, grinding, machining, and other processes which may generate airborne contaminants.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Solid
Color	Silver-gray metallic
Odor	Odorless
Odor Threshold	N/A
pH	N/A
Melting Point	N/A
Freezing Point	N/A
Initial Boiling Point	N/A
Boiling Range	N/A
Flash Point	N/A
Evaporation Rate	N/A
Flammability (solid, gas)	N/A
Upper/Lower Flammability limits	N/A
Upper/Lower Flammability limits	N/A
Explosive Limits	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Relative Density	N/A
Solubility	Insoluble in water
Partition Coefficient: n-octano/water	N/A
Auto-ignition Temperature	N/A
Decomposition Temperature	N/A
Viscosity	N/A

10. STABILITY AND REACTIVITY

Reactivity Chemical Stability	N/A Stable under normal conditions of transport, storage and use for solid formed product.
Hazardous Reactions	Will not occur
Conditions to avoid	N/A
Materials to avoid	Oxidizers. Reacts with strong acids to from explosive hydrogen gas.
Hazardous Decomposition Products	During certain operations such as welding, burning, melting, or hot rolling, metal fumes may be generated. Hexavalent chromium which is a suspect carcinogen may result from pickling of stainless.

11. TOXILOGICAL INFORMATION

Identify likely routes of exposure: Inhalation of dust or fume during welding, burning, melting, cutting, brazing, grinding, machining, milling and other operations.

Inhalation	Yes
Ingestion	Yes
Skin	Yes
Еуе	Yes

Description of delayed, immediate or chronic effects from short term and long term exposure:

Stainless, as a solid, is not toxic and presents no health hazard. Overexposure to dusts and or fumes which may result during processing can pose health hazards as defined below.

Acute Effects of Overexposure:

Inhalation: Inhalation of high concentrations of fumes or dusts may result in irritation and or sensitization of the respiratory track, nasal irritation, and metal fume fever. Eyes: Exposure to fumes and dusts can cause irritation and or sensitization and conjunctivitis.

Skin: Contact with dusts may cause irritation or sensitization leading to dermatitis. Ingestion: Nausea or vomiting may result from ingestion of dusts.

Chronic Effects of Overexposure:

Inhalation: Prolonged inhalation of dust or fume may cause lung, central nervous system, liver, kidney, and nasal cavity damage.

Eyes: Prolonged exposure to fumes and dusts can cause severe irritation, and or sensitization and conjunctivitis.

Skin: Prolonged contact with dusts may cause severe irritation or sensitization leading to dermatitis.

Ingestion: Nausea or vomiting may result from ingestion of dusts.

Iron: Excessive exposure of eyes to airborne iron dust can cause conjunctivitis, choroiditis, and retinitis. Chronic inhalation of high concentrations of iron oxide fume or dust may result in the siderosis (benign pneumoconiosis).

LD50 (oral rat) – 30gm/kg; LC50 – No Data

Nickel: The most common effect resulting from exposure to nickel compounds is "nickel itch", a form of dermatitis is sensitized individuals. Nickel sensitivity, once acquired, may persist indefinitely.

LD50 = 50mg/kg mouse – intravenous. LC50 – No Data

Carcinogenicity: NTP – Reasonably anticipated to be carcinogenic; IARC – Group 1 (there is sufficient evidence for carcinogenicity in humans) and 2B (agents which are possibility carcinogenic to humans); OSHA – Not regulated; ACGIH – A5 (not a suspected human carcinogen)

Chromium: Health hazards associated with exposures are dependent upon its oxidation state. Suspect carcinogen and tumorigen. Dermatitis may result from exposure to chromium fumes.

LD50 (Oral) – No Data; LC50 – No Data

Carcinogenicity: Chromium metal and trivalent chromium compounds are not classifiable as human carcinogens. Hexavalent Chromium (produced by welding, torch cutting, brazing and possibly grinding) is a confirmed human carcinogen. NTP – Group 1 (known to be carcinogenic); IARC – Group 1) there is sufficient evidence for carcinogenicity in humans) and 2B (agents which are possibility carcinogenic to humans); ACGIH – A1 (confirmed human carcinogen).

Manganese: Can affect central nervous system, including languor, sleepiness, weakness, emotional disturbances, spastic gait, recurring leg cramps and paralysis. Upper respiratory system damage may result from inhalation of fume and dust.

LD50 (Oral – Rat) – 30 gm/kg; LC50 – No Data

Molybdenum: Irritation of nose and throat, weight loss and digestive disturbances in animals. Can cause joint pains in the hands, knees, and feet. No industrial poisonings have been reported.

LD50 (Oral) – No Data; LC50 – No Data

Copper: May be responsible for one form of metal fume fever. Metal fume fever's symptoms include cough, headache, fever, nausea, chilling, pain in muscles and joints, and metal taste in mouth. This condition is usually transitory lasting one day or less. Chronic exposure may also result in Wilson's Disease (characterized by hepatic cirrhosis, brain damage. Demyelination, renal disease, and copper deposition in the cornea. LD50 (Oral) – No Data; LC50 – No Data

Silicon: Is an inert material which does not appear to have the ability to cause fibrosis in lung tissue. Silicon may cause chronic respiratory effects.

LD50 (Oral-Rat) - 3160 mg/kg; LC50 - No Data

Aluminum: Inhalation of finely divided aluminum and aluminum oxide powder can cause pulmonary fibrosis and lung damage.

LD50 (Oral) – No Data; LC50 – No Data

Cobalt: Exposure to high levels of cobalt can result in lung and heart effects and dermatitis. An experimental carcinogen.

LD50 (Oral) – No Data; LC50 – No Data

Carcinogenicity: IARC – possibly carcinogenic to humans. ACGIH – animal carcinogen. **Particulates:** Eye and respiratory irritation may occur with exposures to dust.

Medical conditions know to be aggravated by exposure to this material: Persons with lung disorders or diseases or skin disorders may be at added risk as a result of overexposure to this material.

12. ECOLOGICAL INFORMATION (If available)

Not applicable for solid alloy product in its as shipped form. Articles produced from solid product are not an ecological hazard. No information has been found on specific alloy to establish its effect onto the environment if released in a finely divided form. It is believed that finely divided alloy will be hazardous to fish, animals, plants, and the environment. The degree of hazard would depend on the particle size and quantity released. If particle size is small enough, alloy may be ingested by wildlife, with possible toxic effects occurring.

Solid alloy is not expected to migrate easily into soil or ground water. Finely divided alloy can become mobile in water and contaminate soil and ground water. Finely divided alloy may persist in the environment for long periods of time based upon the corrosion resistant, insoluble, and non-biodegradable properties of the alloy. In addition, heavy metals may contaminate the food chain and be consumed by humans.

Some alloy components will react with oxygen to form metallic oxides at varying rates. Iron oxidizes most rapidly in moist air. Metallic particulate discharged to a POTW may pass through or contaminate sewage sludge, may interfere with the treatment system process, and may be non compliant with POTW permit or other regulations.

13. DISPOSAL CONSIDERATIONS (If applicable)

If product as shipped becomes a solid waste, it would not be considered a hazardous waste and should be recycled. Product dusts from processing may be classified as hazardous wastes which are defined within 40 CFR 261 as well as state and or local regulation. Solid waste generated from

product processing should be classified by a competent environmental professional and disposed, processed, or recycled in accordance with federal, state, and local regulation.

14. TRANSPORT INFORMATION (If applicable)

Hazardous Material Proper Shipping Name:	N/A for solid formed product
Hazard Class:	N/A for solid formed product
Identification Number:	N/A for solid formed product

Note: Stainless steel transported in coiled form is under tension and represents a significant source of potential energy due to the tension induced by coiling; it will uncoil to try lay flat in a long strip when banding is cut or other forces are released; uncoiling can be sudden and catastrophic and measures should be taken to ensure that uncoiling will not occur.

15. REGULATORY INFORMATION (If available)

<u>SARA Title III Hazard Categorization:</u> Product (dust and fume) is categorized as an immediate (acute) health hazard and a delayed (chronic) health hazard as defined by 40 CFR 370. Product is not categorized as a fire hazard. Product is not categorized as a reactivity hazard. Product is not categorized as a pressure release hazard.

SARA Title III Section 302 Extremely Hazardous Substances (EHS's): None

SARA Title III Section 312 Reportable Substances:

Nickel, Cobalt, Chromium, Aluminum, Manganese and Copper.

<u>CERCLA Hazardous Substance:</u> (If diameter of released particle >10 micrometers)

Nickel – 100 pound theshold

Chromium – 5000 pound threshold

Copper – 5000 pount theshold

<u>TSCA:</u> The components of this product are listed on the Toxic Substance Control Act Inventory. <u>Pennsylvania R-T-K List:</u>

Aluminum, Manganese, Molybdenum, Nickel, Silicon, Chromium, Cobalt, Copper, and Tantalum.

New Jersey R-T-K Environmental Hazardous Substance List:

Aluminum, Chromium, Copper, Cobalt, Manganese, and Nickel

California Proposition 65:

Listed possible trace elements know by the state to cause cancer – Arsenic (inorganic), Cadmium, Lead.

Listed possible trace elements know by the state to cause reporductive toxicity – Lead Listed components known by the state to cause cancer – Nickel, Cobalt (metal powder) Listed components known by the state to cause reproductive effects - None

16. OTHER INFORMATION

NFPA Rating: Health: 1	Flammability: 0	Reactivity: 0	
HMIS Rating: Health: 1	Flammability: 0	Reactivity: 0	PPE: B

EPA Hazardous Waste Number:

N/A

Note: The percent composition Section 2 reflects the range that is possible within this group of products. These are not the technical specifications for particular product. All grades do not include all hazardous ingredients in section 2.

ABBREVIATION / ACRONYMS

ACGIH	American Conference of Governmental Hygienists
CAS	Chemical Abstracts Service
CFR	Code of Federal Regulations
HMIS	Hazardous Materials Information System
IARC	International Agency for Research on Cancer
mg/m³	Milligrams per cubic meter of air
MSDS	Material Safety Data Sheets
MSHA	Mine Safety and Health Administration
N/A	Not Applicable
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
POTW	Publicly Owned Treatment Work
PPE	Personal Protective Equipment
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time-weighted Average

Date of Revision: 02/20/2023

Soogalu believes that the information and recommendations contained herein (including data and statements) are accurate as of date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Soogalu expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.